



- LEGEND**
- NON-RATED WOOD STUD WALL W/ 2x4 (F) OR 2x6 (F) STUDS AT 16" O.C. W/ 5/8" G&B PAINT.
 - 1 HR FIRE RATED WOOD STUD WALL W/ 2x4 (F) OR 2x6 (F) STUDS AT 16" O.C. W/ 5/8" TYPE A G&B PAINT. SEE DETAIL U.
 - 1 HR FIRE RATED WOOD STUD WALL W/ 2x4 (F) OR 2x6 (F) STUDS AT 16" O.C. W/ 5/8" TYPE A G&B PAINT.
 - 1 HR FIRE RATED WOOD STUD WALL W/ 2x4 (F) OR 2x6 (F) STUDS AT 16" O.C. W/ 5/8" TYPE A G&B PAINT.
 - 1 HR FIRE RATED WOOD STUD WALL W/ 2x4 (F) OR 2x6 (F) STUDS AT 16" O.C. W/ 5/8" TYPE A G&B PAINT.
 - 1 HR RATED 2" CHU WALL W/ 5/8" G&B ON 1/2" FERRING 1 RIGID INSULATION PAINT (PROVIDE SHALLOW BOX OUTLETS).
 - NON-RATED WOOD STUD WALL W/ 2x4 (F) STUDS AT 16" O.C. W/ 5/8" G&B PAINT BRICK VENEER.
 - EXISTING 3 HR FIRE WALL PATCH ANY EX. HOLES OR PENETRATIONS TO MAINTAIN 3 HR ASSEMBLY.
 - 3 HR SHWET WALL - PAINT INTERIOR FLAT WHITE SEE DETAIL W/ 161 ON SHEET A-4.

NOTES: PROVIDE EXPANSION JOINTS IN DRYWALL AT 32'-0" MAX FOLLOWING MANUF. RECOMMENDATIONS.
 PROVIDE SOUND ATTENUATION INSULATION IN ALL WALLS & FLOORS.

2nd FLOOR PLAN
 SCALE: 1/8"=1'-0"
 PROJECT NORTH